

EMERGENCY PROCEDURES

1984 N8323E Cessna 182R

Bold-faced type are immediate action items which should be committed to memory.

Engine Failure During Takeoff Roll

- 1. Throttle.....Idle**
- 2. Brakes.....Apply**
3. Wing Flaps.....
4. Mixture.....Idle Cut Off
5. Ignition Switch.....Off
6. Master Switch.....Off

Engine Failure Immediately After Takeoff

- 1. Airspeed.....**
- 2. 75 KIAS (Flaps Up)**
- 3. 70 KIAS (Flaps Down)**
4. Mixture.....Idle Cut Off
5. Fuel Selector.....Off
6. Ignition.....Off
7. Wing Flaps.....As Required (Full Recommended)
8. Mixture.....Idle Cut Off
9. Ignition Switch.....Off
10. Master Switch.....Off

Engine Failure During Flight (Restart)

- 1. Airspeed.....75 KIAS**
- 2. Carb Heat.....On**
- 3. Fuel Selector.....Both**
4. Mixture.....Rich
5. Ignition.....Both (or START if propeller is stopped)
6. Primer.....In & Locked

Forced Landing w/o Engine Power

1. Seats, Belt, Harness... SECURE
2. Airspeed75 KIAS (Flaps Up)
3. Mixture.....
4. Fuel Selector
5. Ignition
6. Wing FlapsAs Required (Full Recommended)
7. Master Switch
8. DoorsUnlatch prior to Touchdown
9. Touchdown..... Slightly Tail Low
10. Brakes..... Apply Heavily

Precautionary Landing With Engine Power

1. Seats, Belt, Harness... SECURE
2. Airspeed
3. Wing Flaps.....20°
4. Select Field.....Perform Fly Over Inspection
5. Electrical Switches
6. Flaps.....Full on Final Approach
7. Airspeed
8. Avionics & Master Switches . Off
9. Doors.....Unlatched
- Prior To Touchdown
10. Touchdown..... Slightly Tail Low
11. Ignition Switch
12. Brakes..... Apply Heavily

8. Circuit Breakers
9. Faulty circuit (Do Not Reset).....Off
10. Radio Switches
11. Avionics Power Switch
12. Radio/Electrical Switches .. On one at a time w/ delay after each until short is localized.

- Cabin Fire**
- 1. Master Switch.....Off (Leave Ignition On)**
 2. Vents/Cabin Air/Heat..Closed
 3. Fire Extinguisher.....Activate
- Warning**
After discharging an extinguisher within a closed cabin, ventilate the cabin.

4. Land ..As soon as possible and inspect damage
- Wing Fire**
1. Navigation Lights
 2. Strobe Lights.....Off
 3. Pitot Heat
 4. Landing/Taxi Lights
- Note
Sideslip to keep flames away from the fuel tank and cabin, and land as soon as possible using flaps only as required for final approach and touchdown.
- If fire appears out and electrical power is necessary for continuance of flight:
5. Master Switch
 6. Cranking.....Continue



Icing

1. Pitot HeatOn
2. Turn back or change altitude to obtain an outside air temp that is less conducive to icing.
3. Pull cabin heat control to full out and rotate defroster control clockwise to obtain maximum defroster airflow.
4. Increase Engine Speed to minimize ice build-up on propeller blades
5. Watch for signs of carburetor air filter ice and apply carburetor heat as required. An unexplained loss of manifold pressure could be caused by carburetor ice or air intake filter ice. Lean the mixture if carburetor heat is used continuously.
6. Plan a landing at the nearest airport. With an extremely rapid ice build-up, select a suitable "off airport" landing site.
7. With ice accumulation of $\frac{1}{4}$ inch or more on the wing leading edges, be prepared for significantly higher stall speed.
8. Leave wing flaps retracted. With a severe ice build-up on the horizontal tail, the change in wing wake airflow direction caused by wing flap extension could result in a loss of elevator effectiveness.
9. Open left window and if practical scrape ice from a portion of the windshield for visibility in landing approach.
10. Perform landing approach using a forward slip, if necessary, for improved visibility.
11. Approach at 80 to 90 KIAS depending upon the amount of accumulation.
12. Perform a landing in level attitude.

Ditching

1. RadioTransmit Mayday on 121.5 giving location and intentions and squawk 7700.
2. Heavy ObjectsSecure or Jettison.
3. Passenger SeatsMost Upright position
4. Seats and SeatbeltsSecure
5. Flaps20° to 40°
6. PowerEst. a 300 FPM descent at 65 KIAS.
Note
If no power is available, approach at 75 KIAS with flaps up or at 70 KIAS with 10° flaps.
7. Approach
High winds, heavy seasInto the Wind.
Light winds, heavy swells.....Parallel to swells.
8. Cabin DoorsUnlatch
9. TouchdownLevel attitude at established descent rate.
10. FaceCushion at touchdown with folded coat.
11. AirplaneEvacuate through Cabin doors. If necessary, open window and flood cabin to equalize pressure so doors can be opened.
12. Life vests and raftInflate

Airspeeds for Emergency Operations

- Engine Failure After Takeoff:**
Wing Flaps Up -- 75 KIAS
Wing Flaps Down -- 70 KIAS

Maneuvering Speed:

- 3100 Lbs -- 111 KIAS
2600 Lbs -- 102 KIAS
2000 Lbs -- 88 KIAS

Maximum Glide:

- 3100 Lbs -- 76 KIAS
2600 Lbs -- 70 KIAS
2000 Lbs -- 61 KIAS

Precautionary Landing With Engine Power -- 70 KIAS**Landing Without Engine Power:**
Wing Flaps Up -- 75 KIAS
Wing Flaps Down -- 70 KIAS

This checklist is a guide to coordinate Pilot Operating Handbook and STC data applicable to this particular aircraft only. The applicable Pilot Operating Handbook and STC installations remain the official documentation for this aircraft. The pilot in command is responsible for complying with all items in the Pilot Operating Handbook and applicable STCs.

I certify this checklist has been reviewed for accuracy:
L. A. S. / 03/11/06
Wing Director of Maintenance Date
N8322E 060311